



Spec-Coat

High Gloss Acrylic Floor Polish

Spec-Coat is a sacrificial coating designed to protect the interior floor sealer and floor substrate from wear. Spec-Coat provides a stunning gloss that highlights colored, stained or stamped concrete floors while offering excellent slip resistance. The high solids formulation (29%) provides maximum scuff and heel mark resistance, with a high gloss shine. Spec-Coat requires fewer coats than are needed with conventional lower solids products and stays glossy even after numerous cleanings. Created for high traffic areas where resistance to heel marking and scuffing are important.

Spec-Coat is an excellent choice for protecting and enhancing the following interior surfaces:

- Stained Decorative Concrete
- Colored and Stamped Concrete
- Sealed Stone Surfaces
- Linoleum Floors
- Composition Tile Floors

Spec-Coat offers the following benefits:

- Easy Application
- Buffable, Wet or Dry
- High Solids
- Long Lasting
- Heel Mark Resistant
- Slip Resistant
- Re-Coatable
- Non-Yellowing

IMPORTANT NOTE:

Surface can be slippery when wet. Before use on a job, thoroughly test this product on a sample to assure proper performance and appearance. Immediately wipe up pools or puddles where over application has occurred.

LIMITATIONS:

Spec-Coat is not for unsealed porous surfaces, ceramic tile, marble, granite or porcelain. Not recommended for exterior use.

COVERAGE:.....500-1000 sq.ft./gal

SURFACE PREPARATION:

Remove dirt, wax, old floor polish and defective coatings. After cleaning, allow the surface to dry prior to applying Spec-Coat. The surface must be completely clean and dry to the touch. If application is on new unsealed concrete, the surface must be sealed with one of Spec-West's premium sealers. Wait a minimum of 24 hours before applying Spec-Coat to a fresh sealed surface.

APPLICATION:

Apply a light even coat of Spec-Coat with a micro-fiber wax applicator, sponge or clean cloth. Spec-Coat will appear milky when wet and will dry crystal clear. Allow to dry to the touch before walking on the surface or applying an additional coat. Two or more light coats are recommended for the initial application. Additional coats provide added gloss and protection.

CLEAN UP:

When wet, flush with clean water.

DRY SCHEDULE:

15-45 minutes depending on application thickness, ventilation, air and surface temperatures.

MAINTENANCE:

Sweep or dust mop floor regularly. Clean floor with water and if necessary use Spec-Clean at a dilution rate of 9 to 1. Do not use ammonia, ammoniated cleaners or abrasives. Periodic buffing or a light reapplication may be needed in high traffic areas or where scratches have occurred.

TO REMOVE:

Ammoniated acrylic floor polish remover.

TECHNICAL DATA:

VOC.....	<100 g/l
Flash Point.....	>240°F
Weight per Gallon.....	8.6 lbs/gal
Appearance.....	Milky
Odor.....	Mild
Physical State.....	Liquid
Solids by Weight.....	29%

SHELF LIFE and STORAGE:

Store between 35° and 120°F in a sheltered environment, protect from freezing. Material has a one year shelf life.

SAFETY INFORMATION:

CAUTION: LIQUID CONTACT WITH EYES AND SKIN CAUSES IRRITATION. DO NOT INGEST. Contains propylene glycol monobutyl ether, CAS #5131-66-8. Avoid contact with eyes and skin. Wash hands thoroughly after using and before eating and smoking. If spillage has occurred, absorb and dispose of according to local regulations.

FIRST AID:

Should eye contact occur, flush with plenty of water for at least 10 minutes and get medical attention if vision is disturbed. For skin, wash thoroughly with soap and water. If swallowed get medical attention immediately. **DO NOT** induce vomiting.

SHIPPING/HMIS INFORMATION:

Ground/Air/Vessel.....	Not regulated
Required Label	Not required
Required Marking.....	Not required
Uniform Fire Code	Not combustible
HMIS Ratings.....	H-1; F-0; R-0; PP-H

Available in 1 gallon and 5 gallon pails.

PRODUCT WARRANTY:

The statements made herein, on labels, spec-sheets, any of Spec-West's employees or agents concerning this product are given for general information only. Due to variables beyond Spec-West's control in application, surface preparation, surface temperature, humidity and other variable factors, Spec-West assumes no liability for any claim that may arise out of the use of its products and, disclaims any warranty expressed or implied relating to the storage, application, thinning, merchantability, buyers assumption of performance and the fitness for particular purpose. Receipt of products from Spec-West or its agents constitutes acceptance of the terms of this warranty. In the event that Spec-West finds that the product delivered is not of Spec-West's standards of quality, Spec-West will at its sole discretion, either replace the product or refund the full purchase price. Spec-West's choice of one of these remedies shall be the buyer's sole remedy. Spec-West will under no circumstances be liable for consequential damages, except insofar as liability is mandated by law. Spec-West will deliver products at agreed times insofar as it is reasonably able to do so, but will not be liable for failure to deliver on time when the failure is beyond reasonable control.

KEEP THIS PRODUCT OUT OF THE REACH OF CHILDREN



Spec-West Products available through:

10054 Mills Station Rd, Sacramento, CA 95827
800-723-SPEC (7732) or 916-361-1300 Fax 916-361-1381
www.spec-west.com